

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2002-186950

(43)Date of publication of application : 02.07.2002

(51)Int.Cl.

B09B 3/00
C10B 53/00
F23G 5/027
F23G 5/16
F23G 7/00

(21)Application number : 2000-384735

(71)Applicant : UETSUKI MASAHIKO

(22)Date of filing : 19.12.2000


(72)Inventor : UETSUKI MASAHIKO

(54) DRY DISTILLATION TREATMENT METHOD OF ORGANIC WASTE AND EQUIPMENT THEREFOR

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a method for effectively and cheaply treating an organic waste such as agricultural products and processed food stuffs generated from a production place or a supply center of meals, or the like.

SOLUTION: Agricultural products out of the size standards, processed food stuffs, or the like, vegetables of unsold goods, or the like, fagends of breads, leftover rice, beancurd refuse and other organic wastes 1 generated from the production place, the supply center of meals, beancurd shops, or the like, as organic wastes 1 are charged into a dry distillation chamber 3 and are carbonized by heating via a heating chamber 5, wherein a dry distillation gas generated when the organic waste 1 is heated after it is charged into the chamber 3 is introduced into a combustion chamber 4 which heats a heating chamber 5 so as to allow the gas to be combusted at a high temperature to heat the chamber 3, and if the temperature of the chamber 5 exceeds a set value by introducing the dry distillation gas, the volume of the waste 1 charged into the chamber 3 is so reduced as to lower the agitation of the waste 1 to keep the chamber 3 at a predetermined temperature, thus performing a dry distillation treatment on the waste 1.



Particularly, allowing the dry distillation gas to be combusted at the high temperature with an ancillary treatment chamber juxtaposed at the chamber 4 facilitates to perform the dry distillation treatment on the waste 1 containing high protein, high fats and high fats and oils.

LEGAL STATUS

[Date of request for examination] 11.03.2002

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office